MUNTERS PRODUCT INFORMATION

ML Series Desiccant Dehumidifier

Complete Dehumidification Package

ML180

High Efficiency and Reliability

- Desiccant dehumidification – high efficiency, even below 0° C
- Advanced rotor technology – high capacity with economic operating costs
- Internally sealed rotor unit – dehumidifies to low dewpoints
- Hard plastic rotor casing – corrosion resistant construction
- Efficiently designed electrical system – enhanced reliability

Easy Installation and Operation

- Basic control panel – monitors the systems operation status
- Humidistat control – optional control of complete unit or reactivation heater only
- Easily removed access panels – fast installation and service
- Replaceable EU3 filter – enhances air quality
- Unit requires minimal floor area – allows installation in confined spaces
- Duct connections conform to ISO 7807 standards – simplifies air duct installation
- Interchangeable front and back panels – optional dry air installation

Product Description

The ML180 desiccant dehumidifier is designed to efficiently dehumidify in low moisture applications. It is equipped with an internally sealed rotor unit. The rotor casing is constructed of durable thermoset plastic and contains isolated sections that provide a precise balance for dehumidification, reactivation, and heat recovery airflows. Its rugged formed metal frame and access panels are produced from corrosion resistant ALUZINK®.

The electrical control system conforms to EN 60204 (IEC204) standards. The electrical components are mounted on busbars and are constructed of halogen-free plastic. The electrical system is designed for up to 690V and 60° C.

ML Series dehumidifiers conform to both harmonised European Standards and to CE marking specifications.

Munters Rotor Technology

The desiccant rotor is manufactured from a corrugated composite material that is highly effective at attracting and holding water vapour. Every Munters dehumidifier applies a unique rotor technology. Airflows, air conditions, rotor sections, and rotor rotation speeds are optimised for specific applications. An innovative control system maximises the units energy efficiency.

A characteristic of the ML Series rotor technology is an extra rotor sector which provides high capacity, while simultaneously recovering heat, thereby effectively reducing the electrical power requirement.



Munters

Model ML180

Diagram measurements are for reference only.

Scaled and dimensioned AutoCAD drawings are available in Munters' DryCap program.



Width (A)	Depth (B)	Height (C)	Diam. (D)	Diam. (E)	Weight
513 mm	410 mm	910 mm	125 mm	80 mm	53 kg

Dehumidification capacity

Approximate capacity in kg/h.
For more detailed information, please contact your nearest Munters location or refer to Munters' DryCap program.

1. Process air temperature, ºC
2. Process air relative humidity, % RH
3. Dehumidification capacity, kg/h moisture removal kg/hour)



Technical Specifications

Process air[1]
Rated airflow (m³/s) 0,050
Rated airflow (m³/h) 180
Available static pressure (Pa) 200
Fan motor power (kW) 0,25

Reactivation air[1]
Rated airflow (m³/s) 0,019
Rated airflow (m³/h) 67
Available static pressure (Pa) 200
Fan motor power (kW)[2] –

Total power, voltage and current (amps/phase)
Total power (kW) 2,05
115V 1~50Hz (A) 19,5
115V 1~60Hz (A) 19,5
200V 1~50Hz (A) 11,2
200V 1~60Hz (A) 11,2
220V 1~50Hz (A) 10,2
230V 1~50Hz (A) 9,9
240V 1~50Hz (A) 8,5

Reactivation air heater
Heater power (kW) 1,8
Temperature increase across heater(ºC) 95

Miscellaneous data
Operating temperature (ºC) –20/+40
Drive motor power (W) 5
Max noise level unducted (dBA) 75
Air filter, standard EU3
IEC protective class
unit IP44
electrical panel IP54
Winding insulation grade
Fan motor Class F
Drive motor Class F
High temperature cut-out (ºC) 160±5
Amperage rating
remote on relay 2A, 250VAC (max)
alarm contact 2A, 250VAC (max)
Control voltage 24VAC

Options

- Hours run counter (monitors the number of hours the system is operational)
- Humidity control system with alarm and display

  Refer to the RH98 product data sheet
- Air cooled condenser

  Refer to the ML180L product data sheet
- Stainless steel sheet metal casing

[1] Stated performance based on 20ºC and air density of 1,2kg/m³
[2] Common motor for process and reactivation fans

Distributor

Munters Europe AB
www.munters.com

Munters Europe AB
Dehumidification Division
Box 434
S-191 24 Sollentuna
SWEDEN
Tel: +46 8 626 63 00
Fax:+46 8 626 63 65

Subject to change without notice.

DH/MEA/PGBint-0017-08/98

Produced by Wikströms, Uppsala, Sweden
Printed matter. License 341 051